

G-BRLTS-35W-4K



BRILLIANT TS

35W

 Guarantee : 5 years



Initial Data

Power (W)	35
Color Temperature (K)	4000

Product Data

Electrical Characteristics	
Class Of Protection Against Electric Shock (V230)	I
Frequency	50
Input Voltage And Frequency Range (VAC/HZ)	180-265/50-60
Led Module Operating Voltage (V-DC)	36
Led Module Type	Integrated
Nominal Input Current (A@V)	0.160@230
Nominal Input Voltage	230
Power (W)	35
Power Factor	0.95
General Characteristics	
Application	Garden Lighting - Landscape lighting
Application Area	Outdoor

Guarantee (year)	5
Lighting Type	Garden Lighting
Maximum Allowed Humiding (%)	95
Mounting type	pole mounting
Product type	Lighting
Rated Useful Life (L70B10)	100000
Working Temperature Range (C°)	-20~+50
Mechanical Characteristics	
Body Material	Poly carbonate
Diffuser Material	Poly carbonate
Ingress Protection (IP)	IP65
Pipe Holder Diameter (mm)	Ø60
Ral color	white
Type of Power Supply	independent
Weight (Kg)	3.9
Optical Characteristics	
Color Rendering Index	75
Color Temperature (K)	4000
Light Source	SMD LED
Lumen Maintenance Code	9
Luminous Efficiency (Lm/W)	140
Luminous Flux (Lm)	4900
Nominal Power Of Led (W)	1.5
Number Of Leds In The Module (PCS)	48
Sdcm Initial And Value	5SDCM

Dimension

