

G-GRN-80CTZ-10W-3K-1000L-0102X43



GARNET

80

 Guarantee : 3 years



Initial Data

Power (W)	10
Cutout size	80
Dimension (mm)	Ø102x43
Color Temperature (K)	3000
Luminous Flux (Lm)	1000

Product Data

Electrical Characteristics	
Class Of Protection Against Electric Shock (V230)	II
Frequency	50
Input Voltage And Frequency Range	180~265/50~60
Led Module Operating Voltage (V-DC)	35
Led Module Type	Integrated
Nominal Input Current (A@V)	0.087@230
Nominal Input Voltage	230
Power (W)	10
Power Factor	0.5

General Characteristics

Application	Hospitality - Retail:fashion and food stores
Application Area	Indoor
Guarantee (year)	3
Lighting Type	Down Light - Recessed lights
Maximum Allowed Humiding (%)	90
Mounting type	Recessed Ceiling Mounting
Product type	Lighting
Rated Useful Life (L70B10)	70000
Working Temperature Range (C°)	-20~+45
Mechanical Characteristics	
Body Coating	Electrostatic powder paint
Body Material	Die-cast aluminum
Cutout Hole Diameter	80~85
Cutout size	80
Diffuser Material	PS
Dimension (mm)	Ø102x43
Type of Power Supply	independent
Weight (Kg)	0.17
Optical Characteristics	
Color Rendering Index	80
Color Temperature (K)	3000
Light Distribution Angle (degrees)	45
Light Source	COB LED
Lumen Maintenance Code	9
Luminous Efficiency (Lm/W)	100

Luminous Flux (Lm)	1000
Nominal Power Of Led (W)	12
Number Of Leds In The Module (PCS)	1
Sdcm Initial And Value	5SDCM

Dimension

